

ACCESSORIES

PRESSURE SWITCHES FOR OIL AND WATER

DOUBLE FUNCTION PRESSURESWITCHES FOR HEATING OIL	PRESSURE		CONNECTION
	Min.	Máx.	
DSSG-1 with lamp	1,5	4,5	10 mm OD pipe
DSSG-1 without lamp	1,5	4,5	10 mm OD pipe
DSSG-2 with lamp (higher pressure range)	3,7	7	10 mm OD pipe

- Please ask for other pressure ranges.

SINGLE FUNCTION PRESSURESWITCHES FOR HEATING OIL AND WATER	PRESSURE		CONNECTION
	Min.	Máx.	
SS-1A Inverter (Low pressure)	0,3	-	1/4 " (F)
SS-1A	1,2	4,5	1/4 (F)

- Please ask for other pressure ranges.




- Options:
 - Brass nut 10 m/m
 - Brass olive 10 m/m



OIL COLLECTING TRAYS

Metal, Epoxy painted RAL 7032, with fixing clip for infrared leak detector.

MODEL	DIMENSIONES	GRUPOS	Art. Nr.
40	400 x 230 x 60	GP-30 N	21030000004000
62	620 x 230 x 60	GP-30 GE ; GP-70 N ; GP-130 N ; GP-200 N ; GP-300 N ; GP-500 N	21030000006200
92	920 x 350 x 60	GP-70 GE ; GP-130 GE ; GP-200 GE ; GP-300 GE ; GP-500 GE	21030000009200
120	1200 x 350 x 60		2103000001200



EXPANSION VESSELS

MEMBRANE EXPANSIONS VESSELS FOR HEATING OIL	MAX. PRESSURE
1 lts.	3 kg/cm ²
2 lts.	4 kg/cm ²
5 lts.	8 kg/cm ²
8 lts.	8 kg/cm ²
15 lts.	8 kg/cm ²
25 lts.	8 kg/cm ²



- Options:
 - Brass elbow connector 10 x 3/8"
 - Brass elbow connector 15 x 1/2"



INVESTIGACIÓN Y PRODUCCIÓN S.L.