COMPARATIVE TABLE OF THE 3 AUTOMATIC POLISHING PRODUCTS

research * development	SAFA	MINISAFA	MICROSAFA
FLOW RATE	2,000l/h	3,000l/h	20 l/h
FILTRATION	1 particle filter 50µm 1 particle and water absorbent filter 15µm both, type FG-300 aluminium	Particle filter 50µm (strainer) Water decanting filter, type FG-100	Particle filter 100μm Water decanting
Nr. TANKS	Multiple tanks	1 storage tank	1 day tank
RECOMMENDED FOR TANKS	More than 50,000 Lts	Up to 50,000 Lts	Up to 1,000 Lts
PUMP TYPE	Gear pump	Blades pump	Solenoid piston pump
NO FLOW ALARM	Yes	Yes	Yes
WATER ALARM	Yes	Yes	Yes
HIGH PRESSURE ALARM	Yes	No	No
INCLUDES LEAK DETECTOR	Yes	No	No
INGRESS PROTECTION RATING - IP	55	55	66
SUCTION-PRESSURE CONNECTION	1,5" to 2"	1"	1/4"
DIGITAL PRESSURE SWITCH	No	No	Yes
FLOW SWITCH	No	Yes	No
ANALOG PRESSURE SWITCH 0-10bar	Yes	No	No
COUNTER	Yes - MGI 110	No	No
WATER VIEWER	Yes	Yes	Yes
ACHIQUE PUMP	Yes	No	No
MONITORING AND CONTROL BOX TO VALVES	Yes	No	No
PORTABLE VERSION AVAILABLE	Yes	Yes	No
DIMENSIONS	1300x1100x560	500x500x650	400x300x150